





MS COLORFAST45® PAINT SYSTEM


29 & 26 GAUGE



White (30)




Polar White (80)




Light Stone (63)




Mocha Tan (22)




Carlsbad Canyon (10)



Ash Grey (25)




Charcoal (17)




Burnished Slate (49)




Burgundy (15)




Ocean Blue (35)




Forest Green (26)



Fern Green (07) Low Gloss



Patina Green (58)




Native Copper (95)²



Galvalume (41)¹



Patriot Red (73)²



Rustic Steel (W45)²



Red (24)



Red (23) Low Gloss 29 Ga.



Brown (12)




Brown (11) Low Gloss 29 Ga.




MS COLORFAST45® PAINT SYSTEM

29 GAUGE ONLY




Ivory (28)




Dark Blue (21)



Blue (09)



Mocha Brown (13)



Black (06)



★ Meets or Exceeds Steep Slope Energy Star Requirements















¹ Non-Painted Finish

² Upcharge will apply

45 Year Paint Warranty

www.metalsales.us.com

PRODUCT SOLUTION CHART

PANEL	PROFILE	COVERAGE	MS COLORFAST45®		ACRYLIC COATED GALVALUME®	
			29GA	26GA	29GA	26GA
VERTICAL SEAM		12"/16"/18"		◆		●
MINI BATTEN		12"/16"/18"		◆		●
SOFFIT PANEL		12"		●		●
IMAGE II		12"/16"		●		●
PRO-PANEL II®		36"	●	■	●	●
CLASSIC RIB®		36"	●	■	●	●
PBR-PANEL		36"		●		●
IC72-PANEL		36"		●		●
7/8" CORRUGATED		Roof 29 ¹ / ₃ " Wall 32"		●		●
2.5" CORRUGATED		24"		●	●	●
5V CRIMP*		24"	■	■	●	●
U-PANEL*		36"		●		●
SPAN-LINE 36A*		36"		●		●
V-LINE 32*		32"		●		●

Notes:

- For other colors, finishes, gauges, and materials, please inquire
- For Image II panel, refer to Image II panel brochure for color selections
- For panels with asterisk (*) longer lead times will apply

Legend:

- Standard colors are available in any quantity
- ◆ For standard colors, minimum quantity may be required
- Available in limited standard colors

PAINT SYSTEMS

We use high quality paint systems designed to provide long term performance and protection. Each coating is formulated with thoroughly researched, tested and field proven pretreatments, primers, resins, and pigments that can meet your standard and performance requirements.

MS Colorfast45® is a thermoset coating system composed of polyester resin which has been modified with a silicone resin. Much like PVDF finish, the MS Colorfast45 finish offers good protection to the elements with special consideration to chalk and fade resistance, durability, and chemical resistance.

APPLICATION PRECAUTIONS

Avoid installing directly over green or damp lumber, porous insulation, or other damaging materials. The use of a moisture barrier is recommended in such situations. Strong chemicals, such as fertilizer, manure, some soils, and lime may cause damage. Storage or application near such materials should be avoided.

www.metalsales.us.com

STORAGE INSTRUCTIONS

If metal roofing or siding is not going to be used immediately, it should be stored in a dry area. It should be unbundled and stood on end against an interior wall. If materials must be stored outside, protect with canvas or waterproof paper. Allow for air circulation, do not cover air tight.

metal sales
manufacturing corporation



7990 E. I-25, Frontage Road
Longmont, Colorado 80504
800.289.7663 Toll Free
303.702.5440 Phone
800.289.1617 Fax